

Vibraflame®

Cables for extreme temperatures



axon'
cable & interconnect

Vibraflame®

cables for extreme
temperatures

OUR SALES TEAM IS AT YOUR DISPOSAL FOR ANY ADVICE YOU MAY REQUIRE.

THIS CATALOGUE IS INTENDED AS A GUIDE TO HELP SELECTION OF AXON' PRODUCTS.
THE INFORMATION IN THIS CATALOGUE IS ACCURATE TO THE BEST OF OUR KNOWLEDGE AT TIME OF GOING TO PRINT,
HOWEVER, AXON' CANNOT BE HELD LIABLE FOR ANY ERRORS MADE AS A RESULT OF INFORMATION CONTAINED HEREIN.
CHANGES AND MODIFICATIONS CAN BE MADE TO THIS BROCHURE AT ANY TIME WITHOUT PRIOR NOTICE.

Contents

General information	4
The concept	4
Quality	5
Partial of test standards exceeded by Vibraflame® cables	5
Extension and compensating cables for thermocouples	5
Marking and packaging	6
Special cables	6
General applications	6
Customer buying guide	7
Order code	7
Vibraflame® international colour code	8
Table of equivalents	8

Technical data sheets

Single wires

Type BV xxxx	9
Type V xxxx	10
Type RV xxxx	11

Multicore cables

Type BV xxxx V x	12
Type RV xxxx v x	13

Shielded signal cables

Type BV xxxx ST V x	14
Type RV xxxx ST V x	15

Armored multicore cables

Type BV xxxx VS x	16
Type RV xxxx VS x	17

Armored signal cables

Type BV xxxx ST VS x	18
Type RV xxxx ST VS x	19

Large cross section multicore cables

Type V xxxx HS x	20
------------------------	----

VIBRAFLAME® CABLES

Why it pays to use
Vibraflame® cables ?
Vibraflame® cables
will resist higher
temperatures and more
rigorous operating
conditions than any other
kind of flexible cables.
They are ideal for the most
demanding applications in
steel and aluminum plants,
coke mills, glass factories,
oil refineries and offshore
rigs, and in various military
and space installations
and equipment.

General information

Vibraflame® cables work where other cables fail

Vibraflame® cables will maintain electrical circuit integrity at peak temperatures as high as 1565°C. In fires exceeding 1050°C, they will maintain integrity for a minimum of 4 hours. In molten steel or aluminum, they will function for a previously unheard of 15 minutes (min.), allowing you to take steps to prevent costly equipment damage. In addition to heat, Vibraflame® will withstand weather, water, chemicals, acids, and lubricants.

Vibraflame® cables save you money because they last longer and reduce both scheduled and unscheduled downtime

In actual field use, they have proven to last at least 5 times longer than any other heat-resistant cable. Plants generally experience savings of 60% or more during the first year after switching to Vibraflame® cable. In addition, Vibraflame® often makes new, simpler, and money-saving layouts possible. They may, for instance, eliminate the need for protective conduits.

Vibraflame® cables are safer

They contain no asbestos. They are fire resistant and will not propagate flame at any temperature. Their high degree of heat resistance and strength prevents accidents that may be caused by extreme temperatures or spillage of molten metal or glass or inflammable materials. If accidents do occur, Vibraflame® cables give you an extra safety margin of time allowing you to take steps to save equipment, shut down operations, and otherwise minimize the damage and danger to life and property occasioned by industrial accidents.

The concept

Vibraflame® possesses a unique combination of components and construction that no other cable has ever been able to match :

- Insulation: a specially bonded combination of mica, organic polymers (polytetrafluorethylene), and fiberglass (no asbestos) is fire resistant and incapable of propagating flame. It reacts to flame by creating a thermal barrier that protects the conductor and maintains dielectric characteristics.
- Conductor: nickel plated copper provides excellent resistance to oxidation at high temperatures. Vibraflame® also enjoys flexibility.

Quality

Teams of quality control specialists supervise every stage of the Vibraflame® process, and Vibraflame® cables are required to surpass the most exacting standards. Vibraflame® cables more than meet the most rigid international and national tests such as NBN C 30-004 with test conditions of:

- Temperature produced by a gasburner of 900°C ±50°C,
- Duration of 3 hours,
- Mechanical impact every 30 seconds,
- Current leakage not to exceed 1 amp.per conductor,
- Test must be passed by 4 successive samples.



Partial listing of test standards exceeded by Vibraflame® cables

COUNTRY	STANDARD	DURATION	TEST CONDITIONS	
			TEMP.	OTHERS COND.
International	IEC 331	3 H	750°C	In flame
Belgium	NBN C 30-004 § 3.3	3 H	900°C	In flame mechanical impact every 30 sec.
Germany	VDE 0472-814	20 min to 3 H	800°C	In flame



Extension and compensating cables for thermocouples

This range of cables with Vibraflame® insulation will resist temperatures up to 1050°C.

The conductors available include:

- K = Nickel alloy/ Nickel chrome,
- J = Iron/ Constantan,
- T = Copper/ Constantan,
- SX = Copper/ Cupronickel (alloy 11),
- BX = Copper/ Copper alloy,
- E = Nickel chrome/ Constantan.

Should you need any further information, please ask for our “EXTENSION AND COMPENSATING CABLES FOR THERMOCOUPLES” brochure.

AXON' offers engineering assistance & custom design services to advise customers on the cable configurations best suited to their applications.



Marking and packaging

- › Cables are delivered on reels or drums depending on the cable cross section,
- › Minimum ordered quantity: 50 meters.

Special cables

Vibraflame® cables are available in a wide range of configurations including:

- › Coaxials,
- › Triaxials,
- › High voltage cables.

General applications

Examples

- Tundish, offshore oil rigs: power and control cables Fire, blowout, marine & chemical corrosion.
- Overhead cranes (steel plants) : power cables for brakes and motors High temperature, fire, explosion, steel spills.
- Coke oven charging car, pusher and related vehicles for coke batteries: power, control and coaxial cables Extreme temperatures, flames, corrosion, weather.
- Rotary nozzles: power feed cables Operating temperatures : + 1050°C
- Magnetic flux sensor, bof : control cables Extreme heat : + 1400°C
- Electric furnace, bof, blast furnace, plasma furnace: compensating cables Extreme heat.
- Ladle transfer ladle preheater: power cables Heat, fire, steel spills.
- Glassware machinery: power and control cables Fire heat due to hydraulic fluid spills.
- Oil refinery shut-off valve control cables Fire, chemical corrosion.
- Compensation cables for insertion pyrometers Intense heat in a confined space.
- Power lines for electric arc oven sensors Heat in non-circulating air.

Hazards

Customer buying guide

The following data gives you a basic pattern of technical information which is essential to our technical department in order to meet the exact customer requirement:


- Operating temperature,
- Peak temperature,
- Operating voltage,
- Conductor section,
- Precise description of conditions of use (reeled, static, mechanical constraints, stifling or ventilated atmosphere, heating, flame,...).

For any detailed information on the outer diameter of the cables, do not hesitate to contact our sales engineers.



Order code

Example: 6 conductors RV 1619 M twisted - a nickel plated copper braid - a Vibraflame® insulation - a stainless steel armor.



VIBRAFLAME® international colour code

	B	H	F	C	D	L	E	G	J	K
Number of conductors	Black	Blue	Yellow	Brown	Red	White	Orange	Green	Violet	Grey
2	▲	▲								
3	▲	▲	▲							
4	▲	▲	▲	▲						
5	▲	▲	▲	▲	▲					
6	▲	▲	▲	▲	▲	▲				
7	▲	▲	▲	▲	▲	▲	▲			
8	▲	▲	▲	▲	▲	▲	▲	▲		
9	▲	▲	▲	▲	▲	▲	▲	▲	▲	
10	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲

Standard colour of primary wires: red - Standard colour of outer jacket: red.
Special colour coding available on request.

Table of equivalents

AWG	CROSS-SECTION in mm²
2607	0.14
2407	0.226
2207	0.354
2019	0.616
1819	0.962
1619 M (*)	1.229
1619 N (*)	1.34
1419	1.938
1219	3.10
1037	4.74
8133	8.60
6133	13.60
4133	21.70
2665	33.70
1817	41.40
01045	52.95

(*) M: according to MIL specification - N: according to NF specification

Single wires


TYPE BV xxxx

Peak temperatures: -196°C / +400°C

Test voltage: 2200 V RMS

Standard colour: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type BV

AXON' REFERENCE	CONSTRUCTION (Nb x Ø mm)	CONDUCTOR			INSULATED WIRE	
		Ø mm	AREA mm²	LINEIC MAX. RESISTANCE Ω / 100 m	OUTER Ø (mm)	APPROX. WEIGHT (g/m)
BV 2607	7 x 0.16	0.48	0.14	13.62	1.61	5.7
BV 2407	7 x 0.203	0.61	0.226	8.46	1.74	6.8
BV 2207	7 x 0.254	0.76	0.354	5.43	1.89	8.3
BV 0.50	16 x 0.20	0.90	0.50	3.80	2.03	10.0
BV 2019	19 x 0.203	1.01	0.616	3.116	2.14	11.4
BV 0.75	24 x 0.20	1.10	0.75	2.50	2.23	12.7
BV 1.00	32 x 0.20	1.25	1.00	1.90	2.38	15.4
BV 1819	19 x 0.254	1.27	0.962	1.96	2.40	15.2
BV 1619 M*	19 x 0.287	1.42	1.229	1.53	2.55	18.1
BV 1619 N*	19 x 0.30	1.50	1.34	1.40	2.63	18.3
BV 1.50	30 x 0.25	1.50	1.50	1.30	2.63	20.3
BV 1419	19 x 0.36	1.80	1.938	0.96	2.93	25.8
BV 2.50	50 x 0.25	2.00	2.50	0.78	3.13	30.4
BV 1219	19 x 0.455	2.27	3.10	0.60	3.40	37.8
BV 1037	37 x 0.405	2.80	4.74	0.41	3.93	54.9
BV 4.00	133 x 0.20	3.00	4.31	0.45	4.13	49.6
BV 6.00	133 x 0.25	3.80	6.70	0.28	4.93	79.4

(*) M: according to MIL specification - N: according to NF specification

Single wires


TYPE V xxxx

Peak temperatures: -196°C / +1050°C

Test voltage: 2200 V RMS

Standard colour: red

Operating voltage: 600 V RMS



Construction

1 - Conductor: nickel plated copper

2 - Insulation: Vibraflame® type V

AXON' REFERENCE	CONSTRUCTION (Nb x Ø mm)	CONDUCTOR			INSULATED WIRE	
		Ø mm	AREA mm²	LINEIC MAX. RESISTANCE Ω / 100 m	OUTER Ø (mm)	APPROX. WEIGHT (g/m)
V 2607	7 x 0.16	0.48	0.14	13.62	2.05	7.5
V 2407	7 x 0.203	0.61	0.226	8.46	2.18	8.8
V 2207	7 x 0.254	0.76	0.354	5.43	2.33	10.5
V 0.50	16 x 0.20	0.90	0.50	3.80	2.47	12.3
V 2019	19 x 0.203	1.01	0.616	3.116	2.58	13.8
V 0.75	24 x 0.20	1.10	0.75	2.50	2.67	15.2
V 1.00	32 x 0.20	1.25	1.00	1.90	2.82	18.1
V 1819	19 x 0.254	1.27	0.962	1.96	2.84	17.9
V 1619 M*	19 x 0.287	1.42	1.229	1.53	2.99	21.0
V 1619 N*	19 x 0.30	1.50	1.34	1.40	3.07	21.3
V 1.50	30 x 0.25	1.50	1.50	1.30	3.07	23.3
V 1419	19 x 0.36	1.80	1.938	0.96	3.37	29.4
V 2.50	50 x 0.25	2.00	2.50	0.78	3.57	34.2
V 1219	19 x 0.455	2.27	3.10	0.60	3.84	41.7
V 1037	37 x 0.405	2.80	4.74	0.41	4.37	59.9
V 4.00	133 x 0.20	3.00	4.31	0.45	4.57	54.9
V 6.00	133 x 0.25	3.80	6.70	0.28	5.37	85.1
V 8133	133 x 0.287	4.10	8.60	0.23	5.67	99.9
V 10.00	210 x 0.25	4.50	10.50	0.186	6.07	121.0
V 6133	133 x 0.36	5.16	13.60	0.150	7.17	159.0
V 16.00	513 x 0.20	6.15	16.60	0.115	8.16	199.0
V 4133	133 x 0.455	6.50	21.70	0.09	8.51	238.0
V 25.00	361 x 0.30	7.50	25.50	0.074	9.51	292.0
V 2665	665 x 0.254	8.30	33.70	0.06	10.31	363.0
V 35.00	703 x 0.25	8.90	35.60	0.053	10.91	400.0
V 1817	817 x 0.254	9.40	41.40	0.050	11.41	442.0
V 50.00	703 x 0.30	10.50	49.70	0.038	12.51	540.0
V 01045	1045 x 0.254	10.55	52.95	0.035	12.56	555.0

(*) M: according to MIL specification - N: according to NF specification

Thermal protection

Single wires


TYPE RV xxxx

Peak temperatures: -196°C / +1565°C

Test voltage: 2200 V RMS

Standard colour: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type RV

AXON' REFERENCE	CONSTRUCTION (Nb x Ø mm)	CONDUCTOR			INSULATED WIRE	
		Ø mm	AREA mm²	LINEIC MAX. RESISTANCE Ω / 100 m	OUTER Ø (mm)	APPROX. WEIGHT (g/m)
RV 2607	7 x 0.16	0.48	0.14	13.62	2.25	8.0
RV 2407	7 x 0.203	0.61	0.226	8.46	2.38	9.3
RV 2207	7 x 0.254	0.76	0.354	5.43	2.53	11.0
RV 0.50	16 x 0.20	0.90	0.50	3.80	2.67	12.9
RV 2019	19 x 0.203	1.01	0.616	3.116	2.78	14.4
RV 0.75	24 x 0.20	1.10	0.75	2.50	2.87	15.9
RV 1.00	32 x 0.20	1.25	1.00	1.90	3.02	18.8
RV 1819	19 x 0.254	1.27	0.962	1.96	3.04	18.6
RV 1619 M*	19 x 0.287	1.42	1.229	1.53	3.19	21.7
RV 1619 N*	19 x 0.30	1.50	1.34	1.40	3.27	23.4
RV 1.50	30 x 0.25	1.50	1.50	1.30	3.27	24.3
RV 1419	19 x 0.36	1.80	1.938	0.96	3.57	30.0
RV 2.50	50 x 0.25	2.00	2.50	0.78	3.77	35.0
RV 1219	19 x 0.455	2.27	3.10	0.60	4.04	42.6
RV 1037	37 x 0.405	2.80	4.74	0.41	4.57	61.0
RV 4.00	133 x 0.20	3.00	4.31	0.45	4.77	56.0
RV 6.00	133 x 0.25	3.80	6.70	0.28	5.57	86.4

(*) M: according to MIL specification - N: according to NF specification

Multicore cables


TYPE BV xxxx V x

Peak temperatures: -196°C / +400°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded / outer jacket: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type BV
- 3 - Jacket: Vibraflame®

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
BV 2607 V x	AWG 26	2	25
BV 2407 V x	AWG 24	2	24
BV 2207 V x	AWG 22	2	21
BV 0.50 V x	0.50 mm²	2	12
BV 2019 V x	AWG 20	2	12
BV 0.75 V x	0.75 mm²	2	12
BV 1.00 V x	1.00 mm²	2	12
BV 1819 V x	AWG 18	2	12
BV 1619 M* V x	AWG 16	2	12
BV 1619 N* V x	AWG 16	2	12
BV 1.50 V x	1.50 mm²	2	12
BV 1419 V x	AWG 14	2	9
BV 1219 V x	2.50 mm²	2	7
BV 2.50 V x	AWG 12	2	8
BV 1037 V x	AWG 10	2	7
BV 4.00 V x	4.00 mm²	2	7
BV 6.00 V x	6.00 mm²	2	4

x: number of primary wires.

(*) M: according to MIL specification - N: according to NF specification

Multicore cables


TYPE RV xxxx V x

Peak temperatures: -196°C / +1565°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded / outer jacket: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type RV
- 3 - Jacket: Vibraflame®

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
RV 2607 V x	AWG 26	2	19
RV 2407 V x	AWG 24	2	19
RV 2207 V x	AWG 22	2	19
RV 0.50 V x	0.50 mm²	2	12
RV 2019 V x	AWG 20	2	12
RV 0.75 V x	0.75 mm²	2	12
RV 1.00 V x	1.00 mm²	2	12
RV 1819 V x	AWG 18	2	12
RV 1619 M* V x	AWG 16	2	12
RV 1619 N* V x	AWG 16	2	12
RV 1.50 V x	1.50 mm²	2	12
RV 1419 V x	AWG 14	2	7
RV 1219 V x	2.50 mm²	2	7
RV 2.50 V x	AWG 12	2	7
RV 1037 V x	AWG 10	2	7
RV 4.00 V x	4.00 mm²	2	4
RV 6.00 V x	6.00 mm²	2	3

(*) M: according to MIL specification - N: according to NF specification

x: number of primary wires.

Shielded signal cables


TYPE BV xxxx ST V x

Peak temperatures: -196°C / +400°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded / outer jacket: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type BV
- 3 - Braid: nickel plated copper
- 4 - Jacket: Vibraflame®

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
BV 2607 ST V x	AWG 26	2	25
BV 2407 ST V x	AWG 24	2	24
BV 2207 ST V x	AWG 22	2	21
BV 0.50 ST V x	0.50 mm²	2	12
BV 2019 ST V x	AWG 20	2	12
BV 0.75 ST V x	0.75 mm²	2	12
BV 1.00 ST V x	1.00 mm²	2	12
BV 1819 ST V x	AWG 18	2	12
BV 1619 M* ST V x	AWG 16	2	12
BV 1619 N* ST V x	AWG 16	2	12
BV 1.50 ST V x	1.50 mm²	2	12
BV 1419 ST V x	AWG 14	2	9
BV 1219 ST V x	2.50 mm²	2	7
BV 2.50 ST V x	AWG 12	2	8
BV 1037 ST V x	AWG 10	2	7
BV 4.00 ST V x	4.00 mm²	2	7
BV 6.00 ST V x	6.00 mm²	2	4

(*) M: according to MIL specification - N: according to NF specification

x: number of primary wires.

Shielded signal cables


TYPE RV xxxx ST V x

Peak temperatures: -196°C / +1565°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded / outer jacket: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type RV
- 3 - Braid: nickel plated copper
- 4 - Jacket: Vibraflame®

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
RV 2607 ST V x	AWG 26	2	19
RV 2407 ST V x	AWG 24	2	19
RV 2207 ST V x	AWG 22	2	19
RV 0.50 ST V x	0.50 mm ²	2	12
RV 2019 ST V x	AWG 20	2	12
RV 0.75 ST V x	0.75 mm ²	2	12
RV 1.00 ST V x	1.00 mm ²	2	12
RV 1819 ST V x	AWG 18	2	12
RV 1619 M* ST V x	AWG 16	2	12
RV 1619 N* ST V x	AWG 16	2	12
RV 1.50 ST V x	1.50 mm ²	2	12
RV 1419 ST V x	AWG 14	2	7
RV 1219 ST V x	2.50 mm ²	2	7
RV 2.50 ST V x	AWG 12	2	7
RV 1037 ST V x	AWG 10	2	7
RV 4.00 ST V x	4.00 mm ²	2	4
RV 6.00 ST V x	6.00 mm ²	2	3

(*) M: according to MIL specification - N: according to NF specification

x: number of primary wires.

Armored multicore cables


TYPE BV xxxx VS x

Peak temperatures: -196°C / +400°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded / outer jacket: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type BV

- 3 - Jacket: Vibraflame®
- 4 - Armor: annealed stainless steel

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
BV 2607 VS x	AWG 26	2	19
BV 2407 VS x	AWG 24	2	19
BV 2207 VS x	AWG 22	2	19
BV 0.50 VS x	0.50 mm²	2	12
BV 2019 VS x	AWG 20	2	12
BV 0.75 VS x	0.75 mm²	2	12
BV 1.00 VS x	1.00 mm²	2	12
BV 1819 VS x	AWG 18	2	12
BV 1619 M* VS x	AWG 16	2	12
BV 1619 N* VS x	AWG 16	2	12
BV 1.50 VS x	1.50 mm²	2	12
BV 1419 VS x	AWG 14	2	7
BV 1219 VS x	2.50 mm²	2	7
BV 2.50 VS x	AWG 12	2	7
BV 1037 VS x	AWG 10	2	7
BV 4.00 VS x	4.00 mm²	2	4
BV 6.00 VS x	6.00 mm²	2	3

(*) M: according to MIL specification - N: according to NF specification

x: number of primary wires.

Armored multicore cables


TYPE RV xxxx VS x

Peak temperatures: -196°C / +1565°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded / outer jacket: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type RV
- 3 - Jacket: Vibraflame®
- 4 - Armor: annealed stainless steel

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
RV 2607 VS x	AWG 26	2	19
RV 2407 VS x	AWG 24	2	19
RV 2207 VS x	AWG 22	2	19
RV 0.50 VS x	0.50 mm²	2	12
RV 2019 VS x	AWG 20	2	12
RV 0.75 VS x	0.75 mm²	2	12
RV 1.00 VS x	1.00 mm²	2	12
RV 1819 VS x	AWG 18	2	12
RV 1619 M* VS x	AWG 16	2	12
RV 1619 N* VS x	AWG 16	2	12
RV 1.50 VS x	1.50 mm²	2	12
RV 1419 VS x	AWG 14	2	7
RV 1219 VS x	2.50 mm²	2	7
RV 2.50 VS x	AWG 12	2	7
RV 1037 VS x	AWG 10	2	7
RV 4.00 VS x	4.00 mm²	2	4
RV 6.00 VS x	6.00 mm²	2	3

(*) M: according to MIL specification - N: according to NF specification

x: number of primary wires.

Armored signal cables


TYPE BV xxxx ST VS x

Peak temperatures: -196°C / +400°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded / outer jacket: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type BV
- 3 - Braid: nickel plated copper
- 4 - Jacket: Vibraflame®
- 5 - Armor: annealed stainless steel

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
BV 2607 ST VS x	AWG 26	2	19
BV 2407 ST VS x	AWG 24	2	19
BV 2207 ST VS x	AWG 22	2	19
BV 0.50 ST VS x	0.50 mm ²	2	12
BV 2019 ST VS x	AWG 20	2	12
BV 0.75 ST VS x	0.75 mm ²	2	12
BV 1.00 ST VS x	1.00 mm ²	2	12
BV 1819 ST VS x	AWG 18	2	12
BV 1619 M* ST VS x	AWG 16	2	12
BV 1619 N* ST VS x	AWG 16	2	12
BV 1.50 ST VS x	1.50 mm ²	2	12
BV 1419 ST VS x	AWG 14	2	7
BV 1219 ST VS x	2.50 mm ²	2	7
BV 2.50 ST VS x	AWG 12	2	7
BV 1037 ST VS x	AWG 10	2	7
BV 4.00 ST VS x	4.00 mm ²	2	4
BV 6.00 ST VS x	6.00 mm ²	2	3

(*) M: according to MIL specification - N: according to NF specification

x: number of primary wires.

Armored signal cables


TYPE RV xxxx ST VS x

Peak temperatures: -196°C / +1565°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded / outer jacket: red

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper

2 - Insulation: Vibraflame® type RV

3 - Braid: nickel plated copper
- 4 - Jacket: Vibraflame®

5 - Armor: annealed stainless steel

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
RV 2607 ST VS x	AWG 26	2	19
RV 2407 ST VS x	AWG 24	2	19
RV 2207 ST VS x	AWG 22	2	19
RV 0.50 ST VS x	0.50 mm²	2	12
RV 2019 ST VS x	AWG 20	2	12
RV 0.75 ST VS x	0.75 mm²	2	12
RV 1.00 ST VS x	1.00 mm²	2	12
RV 1819 ST VS x	AWG 18	2	12
RV 1619 M* ST VS x	AWG 16	2	12
RV 1619 N* ST VS x	AWG 16	2	12
RV 1.50 ST VS x	1.50 mm²	2	12
RV 1419 ST VS x	AWG 14	2	7
RV 1219 ST VS x	2.50 mm²	2	7
RV 2.50 ST VS x	AWG 12	2	7
RV 1037 ST VS x	AWG 10	2	7
RV 4.00 ST VS x	4.00 mm²	2	4
RV 6.00 ST VS x	6.00 mm²	2	3

(*) M: according to MIL specification - N: according to NF specification

x: number of primary wires.

Large cross section multicore cables


TYPE V xxxx HS x

Peak temperatures: -196°C / +1050°C

Test voltage: 2200 V RMS

Standard colour: single wires colour coded

Operating voltage: 600 V RMS



Construction

- 1 - Conductor: nickel plated copper
- 2 - Insulation: Vibraflame® type V
- 3 - Polyimide tape
- 4 - Armor: annealed stainless steel

AXON' REFERENCE	SIZE CROSS SECTION/AWG	NUMBER OF WIRES	
		MIN.	MAX.
V 8133 HS x	AWG 8	2	5
V 10.00 HS x	10.00 mm²	2	5
V 6133 HS x	AWG 6	2	5
V 16.00 HS x	16 mm²	2	5
V 4133 HS x	AWG 4	2	4
V 25.00 HS x	25 mm²	2	4
V 2665 HS x	AWG 2	2	4
V 35.00 HS x	35 mm²	2	4
V 50.00 HS x	50 mm²	2	2
V 01045 HS x	AWG 0	2	2

x: number of primary wires.

>> BRAZIL

AXON' CABLE INDUSTRIA E COMÉRCIO LTDA

Ed. Corporate Lead Américas - Barra da Tijuca
Av. das Américas, 2480 -Bl. 2
Victory - Salas 111/112
Rio de Janeiro, RJ, CEP 22.640-101
TEL.: +55 21 3596-8002
e-mail: salesbrazil@axon-cable.com

>> CANADA

AXON' CABLE CANADIAN OFFICE

MONTREAL, QUEBEC
TEL.: +1 514 898 2044
e-mail: sales@axoncable.com

>> CHINA

AXON' INTERCONNECT LTD

High Tech Industrial Park,
Chang Bao Xi Road
Ronggui, 528306
SHUNDE, GUANGDONG
TEL.: +86 757 2838 7200
FAX: +86 757 2838 7212
e-mail: sales@axon-interconnect.com

>> GERMANY

AXON' KABEL GMBH

Postfach 1131 - 71201 LEONBERG
Hertichstr. 43 - 71229 LEONBERG
TEL.: +49 7152-97992-0
e-mail: sales@axon-cable.de

>> HUNGARY

AXON' KÁBELGYÁRTÓ KFT

Külső-Szegedi út 104,
H-6000 KECSKEMÉT,
TEL.: +36 76 508 195
FAX: +36 76 508 196
e-mail: axon@axon-cable.hu

>> INDIA

AXON' INTERCONNECTORS AND WIRES PVT LTD

Plot No.102, KIADB Hitech Defense and
Aerospace Park
Unachur Village, B.Marenahalli, Jala Hobli,
Budigere Post
Bangalore North Taluk, Bangalore
Urban-562 129 - Karnataka
TEL.: +91 (0) 806 816 2966
FAX: + 91 (0) 806 816 2999
e-mail: sales@axon-cable.in

DHRUV: your offset partner

>> DHRUV AXON' INTERCONNECT PRIVATE LTD

Plot No.102, SW Part-A,
KIADB Hitech Defense
and Aerospace Park,
Unachur Village, B.Marenahalli,
Jala Hobli, Budigere Post,
Bangalore North Taluk,
Bangalore Urban-562 129. Karnataka

>> JAPAN

AXON' CABLE JAPAN OFFICE

2F-B Marusa Bldg,
1-3-16 Minami Chitose
Nagano-shi, NAGANO,
380-0823 JAPAN
TEL./FAX: +81 26 217 6728
e-mail: axon-japan@axon-cable.com

>> LATVIA

AXON' CABLE SIA

Višķu iela, 21 C
LV-5410 DAUGAVPILS
TEL.: +371 6540 78 91
e-mail: axon@axoncable.lv

>> MEXICO

AXON' INTERCONEX, S.A. DE C.V.

Av. Peñuelas 21-A1.
Industrial San Pedrito Peñuelas
Querétaro Park
76148 Querétaro, Qro.
TEL.: +52 442 215 2713
e-mail: axon-mexico@axoncable.com

>> SINGAPORE

AXON' CONNECT PTE LTD

50 Gambas Crescent,
Proxima@Gambas,
#08-08 SINGAPORE 757022
TEL.: +65 62 50 31 69
e-mail: sales.singapore@axon-cable.com

>> SPAIN

AXON' CABLE SPANISH OFFICE

C/Capitán Haya, N°1, Planta 15
28020 MADRID
TEL.: +34 91 418 43 46
FAX: +34 91 556 28 80
e-mail: sales@axon-cable.com

>> UNITED KINGDOM

AXON' CABLE LTD

AXON' AGORA - Admiralty Park
ROSYTH DUNFERMLINE
FIFE KY11 2YW
TEL.: +44 1383 421500
e-mail: sales@axon-cable.co.uk

>> USA

AXON' CABLE INC.

1316 N Plum Grove Road
SCHAUMBURG, IL. 60173
TEL.: +1 847 230 7800
e-mail: sales@axoncable.com

VISIT OUR WEBSITE
www.axon-cable.com



FOLLOW US



HEADQUARTERS >> France

>> AXON' CABLE S.A.S.

ROUTE DE CHALONS EN CHAMPAGNE - 51210 MONTMIRAIL
TEL : +33 3 26 81 70 00 - FAX : +33 3 26 81 28 83
e-mail : sales@axon-cable.com - <http://www.axon-cable.com>

axon'
cable & interconnect